

A3

Digital inkjet printer

NC-UVA3MAX desktop small UV digital inkjet printer has the advantages of high precision, small volume, diversification, intelligence, easy operation, multi-function, strong stability, high cost performance, etc. It is not limited by materials, and it is multi-purpose and easy to realize personalized creation.


 **ARVANITISHOP**



Product parameters

Model number	NC-UVA3MAX	
Print head	Epson I3200-U1HD*1	
Nozzle spray force range	2-3mm	
Number of nozzles	3200个	
Distance between nozzles	3200 (Individual)	
Number of nozzle rows	8	
Maximum number of supported ink colors	8	
Nozzle physical resolution	300npi/1 List, 600npi/2 List, 1200npi/4 List	
Effective printing width	33.8mm	
Droplet ejection performance (droplet volume and ejection frequency)	2 levels of grayscale 5pl (43.2kHz)	
	3 levels of grayscale 6.0-12.5pl (21.6kHz)	
	4 levels of grayscale 3.8-6.2-9.3pl (21.6kHz)	
Corresponding ink viscosity	5-7mPa.s	
Print size	297*420mm	
Print height	0-90mm	
Print version	White and color and varnish print at same time	
Print mode	CMYK+W+V/CMYKLcLm+W/CMYKLcLmLkLlK/CMYK	
Resolution	960*1200dpi / 960*960dpi	
Printer dimension	L*W*H	1000mm*902mm*592mm
N.W.	78KG	
Packing size	L*W*H	1.11m*1.01m*0.76m
G.W.	110KG	
Rip software	Future Rip	
Flat printing speed (A3 format)	High-precision mode (8pass)	9-34 minutes/version
	Standard mode (6pass)	7-33 minutes/version
Graphic format	Tiff,Jpg,Eps,Pdf	
Connection method	Network cable	
Power	AC220/110V, 50HZ~60HZ	
Rated power	140W	
Working environment	Temperature	20°C-28°C
	Humidity	35%-65%
Ink type	Environmental UV curing ink	
Printer type	Digital inkjet printer	

Fixture optional

Rolling fixture			
Material thickness	0.2-0.5mm		
Roll Paper Specifications	weight	Within 10kg	
	width	30-250mm	
	diameter	Within 150mm (three-inch core, 75mm)	
Material length	50m/roll		
Applicable material	Kraft paper stickers, white paper stickers, transparent stickers, coated paper stickers, glossy gold/silver stickers, brushed gold/silver stickers, coated paper, glossy silver paper, double-transparent labels, matte Film weak solvent PP adhesive, PET film, pvc transparent film,		
Roll printing speed	High-precision mode (8pass)	9-34 minutes/version	
	Standard mode (6pass)	7-33 minutes/version	
Roll fixture package size	415mm*350mm*105mm		
Roll fixture package weight	4.5KG		
Electric cylinder fixture			
Cylinder diameter	25-80mm		
Cylinder length	20-210mm		
Applicable material	Paint cup, stainless steel, plastic, glass, ceramic, wood, acrylic, etc.		
Round bottle printing method	White color (round bottle mode does not support varnish printing)		
Round bottle printing speed	One-fourth mode	5-7minutes/piece	
	One-sixth mode	7-10minutes/piece	
	One-eighth mode	8-11minutes/piece	
Cylindrical fixture packing size	345mm*323mm*80mm		
Cylindrical fixture packing weight	2.6KG		